

Daniamant design and manufacture all of our products in line with the relevant worldwide approvals, technical specifications, current legislation and International directives.

Our mission is to achieve World class performance through partnerships with our suppliers, customers and employees, providing products and services that enhance the safety and security of our customers.

Daniamant products cover 11 key areas:

- Lifejacket Lights
 - Liferaft Lights
- Lifebuoy Lights
- Intrinsically Safe Lights
 - Special Lights
- LED FlaresBridge Navigational Watch
- Alarm System (BNWAS)
 - SalinometersOil Level Alarm
- Electronic Inclinometer
- Agency for a range of world-renowned safety product brands (supplied to the Danish market)

Further Information

For further information on our products, please see our website: www.daniamant.com

Daniamant Ltd

Unit 3, The Admiral Park Airport Service Road Portsmouth, PO3 5RQ United Kingdom

Tel +44 23 92 67 51 00 Fax +44 23 92 67 51 01 sales@daniamant.com



Lifeboat Light SL-400 / SL-450

Introduction

The SL-400, previously supplied and manufactured by Jotron (Part No. 86240) is now joined by the SL-450. This provides the same great Lifeboat Light in an alternative low profile form.

Features

- 10-30v DC external power
- Flange mount
- >4.3 Candela light intensity
- SOLAS approved
- Sealed, small and compact
- Robust
- Flash: 50-70 flash/min

The SL-400 / SL-450 are high quality external Lifeboat Lights designed to build on the very successful Rescue Master range that is still produced today. The SL-450 has been introduced to assist installation where space above the survival craft is restricted.

It is designed to be fitted on motorised survival craft and to be connected to the craft's 12v electrical system.

The SL-400 / SL-450 Lifeboat Light uses the latest advances in LED technology. It features very low current consumption and enhanced reliability.

The products comes with a standard 4 metres length of cable which can be cut down to suit the craft's requirement.

Installation

Use stainless steel screws, mounting must be on a flat surface to prevent water-ingress. Connect the cable to the external power-supply (10-30v DC), observing correct polarity.

Dimension details can be found on our Technical Data Sheet for more information.

Polar Code

The SL-400 and SL-450 have been tested against the Polar Code to -52 $^{\circ}$ C for use in polar regions. Please see the product page on our website for a Statement of Test.